



Gillison's Variety
Fabrication, Inc.

Manufacturers of quality farm equipment since 1977.

**GVF
ORBIT LIFT
PRUNING TOWERS
12', 16', 20', 25'**

For over thirty years we have been improving, tweaking and re-designing our pruning tower to offer you the most dependable, safe and rugged product. This is why we and many others agree, the GVF Orbit Lift Pruning Tower is the best in the industry.

Powerful • Rugged • Dependable • Safe



Advanced Hydrostatic Drive offering Enhanced Mobility

We have developed a tandem hydrostatic drive system that allows for improved ground drive control. Direct drive radial piston motors power each wheel independently eliminating power stall and increasing speed range. Wheel motors also have integrated parking brakes.



Easy Entry Operator's Platform



- Large 19" door opening.
- Low step height.
- Safety latch on door.
- Safety harness hook.
- All controls located inside.
- Ergonomic work space.
- Fully enclosed platform with padding around the edges.
- Heating & cooling options.

Standard Features Include:

- Convenient flip-up hood on both sides for easy access.
- Kubota 3 cyl. diesel engine.
- 4 mph travel speed.
- Great torque, 55% grade ability.
- Two individual 31 - 15.50 -15 wheel drives for greater maneuverability in any position.
- 25' lift offers a standard hydraulic sliding axle that makes it easier for you to go quickly from working to transporting the lift.
- Ignition switch located in the operator's platform.
- Operation controls located in the center of the platform for easy use by either hand.
- Single hand joystick for true proportional drive control in any direction.
- Pruner/Saw selector located next to joystick for one hand operation.
- 2-speed electric throttle control.
- Tool rack for pruner and saw with quick disconnects.
- Special pivoting wheel on the rear of the machine is key to maneuverability.
- Large 15 gallon external fuel tank for increased operation time.
- Oil cooler comes standard.
- Rugged chassis design built for durability and stability.
- Heavy duty boom and leveling arm with only 3 hoses running to platform. Hoses are plumbed through steel tubing.
- Tow tongue is carried on the machine at all times and towing is simply accomplished with a flip of a switch.
- Adjustable boom cradle.

Safety

Safety is important, and we do our best to design and deliver a safe pruning tower.

- Some safety features include:
- A strong, fully fabricated boom.
 - An enable switch that must be stepped on for directional controls to be operational.
 - Lift over-ride functions located at the engine controls.
 - Secure, fully enclosed operator's platform with safety latch and safety harness hook.
 - Weather proof owner's manual storage container located on chassis.

Hydraulic Axle Slides

Our slides are fully enclosed inside the steel frame to protect cylinders and plumbing. The slide is controlled by a switch located in the operator's platform to easily slide on the go.



New Tracks Option!

Get unmatched performance with the tracks option! These tracks offer increased traction and more power. They are just what you need in steep terrain.

Options:

- Available with a picking basket.
- Heating and cooling option for operator's platform.
- Available with tracks.
- Storage cover available for the operator's platform.



Hydraulic sliding axle for 25' lift.



Flip up hood on both sides.

GVF Orbit Lift Specifications

	12'	16'	20'	25'
Weight	1975 lbs.	2075 lbs.	3040 lbs.	3450 lbs.
Width	8'	8'	10'	10' transport 13' working
Length	15'	20'	22' 5"	24'
Height	65"	65"	72"	94"
Bucket Floor Ht.	18"	18"	18"	18"